

RESULTS AND PERSPECTIVES

ATIC Leuven 14 April 1016

Jean Lebrun (JCJ)





Consider all steps of building life cycle:

- Design
- Commissioning
- Management
- Audit
- Retrofit

Design

- The building
- The HVAC plant
- « Primary » and « secondary » units
- Chillers, cooling towers, other heat exchangers...and « auxiliary » components!
- Inside each chiller: compressors, evaporators, condensers...
- Simulate!





EES Professional: D:\Archives extraits JL1603047\JL160104\Annexe 59 JL160104\Reference case Frankfurt JL150519-04 corrected.EES - [Diagram Window]

File Edit Search Options Calculate Tables Plots Windows Help Examples



Calculate

$$\tau_{\text{winter},1} = 0 \text{ [h]}$$

$$\tau_{\text{winter},2} = 8760 \text{ [h]}$$

$$\Delta\tau_{\text{winter}} = 0.5 \text{ [h]}$$

$$t_0 = 20 \text{ [C]}$$

$$Q_{\text{preheatingcoil,kWh}} = 371932 \text{ [kWh]}$$

$$Q_{\text{postheatingcoil,kWh}} = 98547 \text{ [kWh]}$$

$$Q_{\text{TUheatingcoils,kWh}} = 21527 \text{ [kWh]}$$

$$Q_{\text{boiler,kWh}} = 483582 \text{ [kWh]}$$

$$Q_{\text{gas,consumed,kWh}} = 563486 \text{ [kWh]}$$

$$\eta_{\text{boiler,HHV,average}} = 0.8582 \text{ [-]}$$

$$Q_{\text{cooling,AHU,kWh}} = 81592 \text{ [kWh]}$$

$$Q_{\text{TUcoolingcoils,kWh}} = 598596 \text{ [kWh]}$$

$$Q_{\text{evaporators,kWh}} = 766753 \text{ [kWh]}$$

$$W_{\text{chillers,kWh}} = 285190 \text{ [kWh]}$$

$$\text{COP}_{\text{average}} = 2.689 \text{ [-]}$$

$$Q_{\text{sun,kWh}} = 340658 \text{ [kWh]}$$

$$Q_{\text{s,occ,kWh}} = 165361 \text{ [kWh]}$$

$$W_{\text{light,kWh}} = 634279 \text{ [kWh]}$$

$$W_{\text{appl,kWh}} = 599046 \text{ [kWh]}$$

$$W_{\text{total,kWh}} = 1.768\text{E}+06 \text{ [kWh]}$$

$$W_{\text{mainfan,kWh}} = 63462 \text{ [kWh]}$$

$$W_{\text{returnfan,kWh}} = 21968 \text{ [kWh]}$$

$$W_{\text{TUfans,kWh}} = 68724 \text{ [kWh]}$$

$$W_{\text{heatingpumps,kWh}} = 8423 \text{ [kWh]}$$

$$W_{\text{coolingpumps,kWh}} = 86565 \text{ [kWh]}$$




for HVAC professionals


2:40 PM
4/14/2016

EES Professional: D:\Archives extraits JL1603047\JL160104\Annexe 59 JL160104\Reference case Frankfurt JL150519-04 corrected.EES - [Plot 2]

File Edit Search Options Calculate Tables Plots Windows Help Examples



Plot 1 Plot 2




2:44 PM
4/14/2016
FRA

for HVAC professionals

Comissioning


- Characteristics and functional performance verifications
- Correcting actions
- Tuning and balancing
- Reception procedures
- Analysis


Example of correcting action



Management

- Optimal control (example: cooling tower fan...)






Audit

- Use main components as measuring device (including the refrigeration compressors!)

Back to some questions and facts...

A Typical Chiller's Carbon Footprint


98% of the total global warming impact is indirect emissions of CO₂ due to electric energy usage, production and disposal of the equipment



- 
- That is why air cycles reverse Brighton cycles are of little interest here!

Oil free enables multiple compressor benefit

Multiple oil-free compressors improve energy efficiency at low load operation



I. The interest behind variable speed compressors

- Comfort application runs most of the time at part load*

	ESEER parameters		
Part Load Ratio	Air temperature (°C)	Water temperature (°C)	Weighting coefficients
100	35	30	3 %
75	30	26	33 %
50	25	22	41 %
25	20	18	23 %


ESEER is calculated as follows:

$ESEER = A.EER_{100\%} + B.EER_{75\%} + C.EER_{50\%} + D.EER_{25\%}$

With the following weighting coefficients:

A = 0.03 ; B = 0.33 ; C = 0.41 ; D = 0.23

Importance of
part load
efficiency



- Better capacity modulation
- Start/stop's reduced considerably
- Lower inrush current

Up to 45% reduction

Starting current reduced by 5

CO₂ comme réfrigérant

Désavantages:

- Des niveaux de pression relativement élevés
- Les aspects de sécurité (règlements) et la conception des composants
- Équipement pour éviter des **pressions excessives** pendant les périodes d'arrêt!!!
- **Température critique à 31,1 ° C**
propriétés thermodynamiques défavorables pour les systèmes avec des températures de sortie des pressions de refoulement plus élevées / de refroidisseur de gaz

HC comme réfrigérant

Désavantages:

- Inflammable et explosif "Safety Group A3«
 - Des mesures de sécurité spécifiques (exigeant des règles de sécurité)
 - l'augmentation des coûts d'investissement
 - les questions de responsabilité (conception, installation, d'exploitation et de service!)
 - limitations de charge et de l'emplacement de l'installation
 - peut nécessiter des boucles secondaires. Augmentation des besoins en énergie et les coûts d'investissement
- **Particulièrement forte solubilité avec des huiles de réfrigération habituelles**
 - Forte dilution et l'effet solvant
 - Caractéristiques de lubrification défavorables
 - Danger d'une usure excessive et réduit la durée de vie
 - Exige des mesures supplémentaires, comme une supérieur de viscosité d'huile, résistance carter plus forts (sécurité!), cycle pompe a vide, échangeur de chaleur interne.

System optimisation

- Operational considerations
- “Free” Cooling ???
- COP objectives / water consumption
- Lay out flexibility
- ROI / TCO analysis

In (very) short..

- Look to global (direct + *indirect*) Impact
- Look to the **whole** HVAC system
- Include reliable **simulation** at design stage
- Make **corrections** on site
- Include real **optimization** in the management
- Use compressors (and other components as **measuring devices**)

- Thank you for your attention!